

DATA SHEET

SENIOR/S-2200 VA
SENIOR/S-2400 VA
SENIOR/S-2500 VA
SENIOR/S-2600 VA
SENIOR/S-2800 VA
SENIOR/S-3000 VA



Fully automatic twist wrapping machine for all kinds of profiles and long products with high production capacity in modular design. Conveyor technology is adapted specifically to the product (e.g. roller track, belt or chain conveyor).

Industries/applications

All kinds of long products and profiles complying with the dimensions specified below.

Your benefits

- high efficiency
- wide range of applicability
- divergent products can be packed in bundles or entirely wrapped to convenience
- no risk of product damage
- extremely low cost of consumables and energy
- machine operating at low noise level
- no set-up times required
- modular design
- product specific conveyor technology
- integration in production lines possible

Product dimensions

Model	SENIOR/S-2200 VA	SENIOR/S-2400 VA	SENIOR/S-2500 VA
Width:	200 - 2,000 mm	200 - 2,150 mm	250 - 2,250 mm
Height:	100 - 1,850 mm	100 - 1,950 mm	100 - 2,050 mm
Max. cross-section diagonal:	2,100 mm	2,300 mm	2,400 mm

Model	SENIOR/S-2600 VA	SENIOR/S-2800 VA	SENIOR/S-3000 VA
Width:	300 - 2,350 mm	300 - 2,450 mm	300 - 2,600 mm
Height:	100 - 2,100 mm	100 - 2,200 mm	100 - 2,400 mm
Max. cross-section diagonal:	2,500 mm	2,700 mm	2,900 mm

Length of wrapping material: 500 mm to unlimited

SENIOR/S-2200 VA
SENIOR/S-2400 VA
SENIOR/S-2500 VA
SENIOR/S-2600 VA
SENIOR/S-2800 VA
SENIOR/S-3000 VA

Wrapping/packaging materials

PE stretch film, VCI stretch film, PE film, crepe paper, etc.
Width: up to 500 mm
Core diameter: 76 mm

Specifications

Dimensions (width x depth x height): depending on the specific design
Control voltage: 24 VDC
Line voltage: 400 V – 50 Hz, 3-phase

Options

This customer-oriented solution can be adapted to almost any project requirements.
Also available with other wrapping material dimensions (125, 165, 250 or 500 mm).
Also available as total pack (6 side packaging).

Further features

The machine can be delivered conforming to CE guidelines and according to the latest technical guidelines for industrial machinery.
Further, the machine can be integrated into an overall safety concept without protective fence.

(Technical modifications reserved)

SENIOR/S-2200 VA
SENIOR/S-2400 VA
SENIOR/S-2500 VA
SENIOR/S-2600 VA
SENIOR/S-2800 VA
SENIOR/S-3000 VA

Machine drawing (example)

